

Hempel's Paint Stripper 69560

Product characteristics

Description

Hempel's Paint Stripper is a highly effective, solvent based paint remover which can be used on most painted or varnished surfaces.

Recommended use

Recommended to remove old paint and varnish.

Features

- Can be applied on most types of paint, incl. silicones.

Product safety

VOC content

Legislation	Value
EU	311 g/L [2.60 lb/US gal]

According to specific legislation, see details in the Explanatory Notes available at Hempel website, hempel.com or at your local Hempel website.

Handling

Handle with care. Before and during use, observe safety labels on packaging and paint containers and follow all local and national safety regulations. Always consult Hempel's Safety Data Sheet for this product along with the Product Data Sheet.

Product data

Product code

69560

Standard shade / code

Transparent 00000

Volume solids

0 ± 2%

Specific gravity

1 kg/L [8 lb/US gal]

Surface preparation

Maintenance and Repair

- It is recommended a small test patch be performed prior to application and the duration of treatment required is noted.

Application

Thinner

No thinning

Application method

Tool	Thinning max vol.
Brush/Roller	No thinning

Do not apply in direct sunlight.

Application conditions

- Do not use hot air pistols. Keep away from flames and hot surfaces.
- Temperature of product must be above 10°C [50°F] during application.

Hempel's Paint Stripper 69560

Application remarks

- Apply the product liberally with brush or roller to a dry surface. Do not treat too large an area in one step. Cover the treated area with aluminium foil to prevent excessive evaporation of the active solvents. Leave to work for 30-45 minutes until the paint coat dissolves or lifts. Shortest duration for antifoulings, alkyd paints and varnishes, longest for silicone and epoxy. Use with caution on glass fibre and plastics (may harm thermoplasts). Scrape off old paint and clean with hot water and a boat shampoo. Old and thick coats may need a repeat treatment.

Drying and overcoating

Storage

Shelf life

Ambient temperature	25°C [77°F]
Product	60 months

Shelf life from date of production, when stored in original, unopened containers. Thereafter, the product quality must be re-inspected. Storage at elevated temperatures may reduce shelf life. For advice, please consult Hempel.

Additional documents

Additional information is available at the Hempel website <https://www.hempel.com/service-and-support/technical-guidelines> or at your local Hempel website:

- Explanatory Notes for Product Data Sheet.
- Application methods.
- Further information: Hempel Yacht Paint Manual and hempeleyacht.com

This Product Data Sheet ("PDS") relates to the supplied product ("Product") and is subject to updating from time-to-time. Accordingly, the buyer/applicator should have regard to the PDS supplied together with the relevant batch of the Product (and not an earlier version). In addition to the PDS, the buyer/applicator may receive some or all of the following specifications, statements and/or guidelines as listed below or as are available from the Hempel website under 'Products' at www.hempel.com (the "Additional documents"):

No.	Document description	Location/comments
1.	Technical Statement	One-off specific advice provided on request for specific projects
2.	Specification	Only issued for specific projects
3.	PDS	This document
4.	Explanatory Notes to the PDS	Available at www.hempel.com and contain relevant information about the Product testing parameters
5.	Application Instruction	Where available, at www.hempel.com
6.	Generic technical guidelines (e.g. on application and surface preparation)	Where available, at www.hempel.com

In the event of a conflict of information between the PDS and the Additional documents, the order of priority of information shall be in the order as set out above. In such event you should also contact your representative at Hempel for clarification. Furthermore, the buyer/applicator must have full regard to the relevant Safety Data Sheet provided with each Product and which can also be downloaded from www.hempel.com.

Hempel shall not be liable for defects where the application of the Product has not been made fully in accordance with the recommendations and requirements set out in the relevant PDS and the Additional Documents. The information and terms of this disclaimer apply to this PDS, the Additional documents and any other documents supplied by Hempel in respect of the Product. In addition, the Product is supplied and all technical assistance is given subject to Hempel's General Conditions of Sale, Delivery and Service, unless otherwise expressly agreed in writing.